



Main

Range of product	Asfora
Product or component type	Roller blind push-button
Device presentation	Complete product
Colour tint	White
Type of packing	Flow-pack

Complementary

Switch function	Roller blind
Device mounting	Flush
Power range	2300 W
Rated current	10 A 250 V AC
Marking	UP-DOWN
Connections - terminals	Screwless terminals
Number of cables	2 x 2.5 mm ²
Cable stiffness	Rigid Flexible
Wire stripping length	12 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws 51...80 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	15 mm
Product weight	0.104 kg

Environment

Standards	IEC 60669-1
Product certifications	UKR VDE TSE

Quality labels	CE
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1639 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructio	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------