



### Main

|                           |                  |
|---------------------------|------------------|
| Range                     | Asfora           |
| Product or component type | Switch           |
| Device presentation       | Complete product |
| Colour tint               | Aluminium        |
| Type of packing           | Flow-pack        |

### Complementary

|                         |                                       |
|-------------------------|---------------------------------------|
| Switch function         | 1-pole                                |
| Device mounting         | Flush                                 |
| Power range             | 2300 W                                |
| Rated current           | 10 AX 250 V AC                        |
| Marking                 | Without marking                       |
| Connections - terminals | Screwless terminals                   |
| Number of cables        | 2 x 2.5 mm <sup>2</sup>               |
| Cable stiffness         | Flexible<br>Rigid                     |
| Wire stripping length   | 12 mm                                 |
| Material                | ABS (acrylonitrile butadiene-styrene) |
| Surface finish          | Painted                               |
| Conductor material      | Copper                                |
| Fixing mode             | Claws 51...80 mm                      |
| Height                  | 83 mm                                 |
| Width                   | 83 mm                                 |
| Depth                   | 42 mm                                 |
| Projecting depth        | 15 mm                                 |
| Product weight          | 0.091 kg                              |

### Environment

|                        |              |
|------------------------|--------------|
| Standards              | IEC 60669-1  |
| Product certifications | Aenor<br>VDE |

|                         |      |
|-------------------------|------|
| Quality labels          | CE   |
| IP degree of protection | IP44 |

### Offer Sustainability

|                                |   |
|--------------------------------|---|
| Sustainable offer status       | Not Green Premium product   |
| RoHS (date code: YYWW)         | Compliant - since 1642 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                          | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product end of life instructio | Need no specific recycling operations   |